

Sephora Pendant product codes

	Codes	Example
Family		
Sephora	SEP	SEP
Style		
Radius	RA	RA
Cubis	CU	
Mounting		
Pendant Easyfit™	PEN	PEN
Light engine		
Performance	PE	CO
Colour temperature		
2700K	27	30
3000K	30	
4000K	40	
Distribution		
Wide road - Diamond+ A Optic (A1)	A1	C3
Footpath - Diamond+ B Optic (B1)	B1	
Area - Diamond+ C Optic (C2 / C3)	C2 / C3	
Standard road - Diamond+ D Optic (D1)	D1	
Drive current		
The Performance engine is constant current and can be run at drive currents from 75mA to 800mA are available in 25mA increments.		080
Insert drive current in 3-digit format	eg 250mA = 250	
Product colours		
RAL 9016 White	40	DB
RAL 9005 Black	10	
RAL 9006 Aluminium	26	
RAL 9007 Metallic grey	27	
DB 703 Metallic dark grey	DB	
Corten brown	CB	
Control		
No photocell	N	IUC
Photocell 35 lux (1:0.5)	U	
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
Integral CMS - Urban Control	IUC	
Integral CMS - Telensa	ITE	
Integral CMS - Mayflower	IMA	
<i>Pre-programmed dimming [1]</i>		
Example code = SEP RA PEN CO 30 SY 080 DB IUC		

[1] Available as standard subject to further information being provided at time of order.

For further help with specifying a product, please [contact us](#)