



## Sample Specification Text

Aventis Plain wall luminaire with LED light engine and output of 2,100lm with 3,000K colour temperature. Fixed output DALI driver operating at 500mA. Die-cast aluminium body in RAL 7046 mid grey with a polyester powder coat finish and frosted polycarbonate glazing. IP65 and IK08 protection. For -25 °C to +40 °C ambient operating temperatures. Class I.

## Performance

<b>Output (luminaire flux)</b>	2,100lm (max)
<b>Power</b>	19W (max)
<b>Efficacy</b>	111lm/W (max)
<b>Colour Temperatures</b>	3000K 4000K
<b>Colour Rendering Index (CRI)</b>	> 80
<b>Distributions</b>	Symmetric
<b>Certifications</b>	UKCA, CE

## Mechanical

<b>Mounting Options</b>	Wall mount
<b>Glazing</b>	Frosted polycarbonate
<b>Housing</b>	Die-cast aluminium
<b>Colours</b>	Mid Grey RAL 7046 Black RAL 9005
<b>Finish</b>	Polyester powder coat Marine-grade C4 coating
<b>IP Rating</b>	IP65
<b>IK Rating</b>	IK08
<b>Weight</b>	2.4kg

## Electrical

<b>Driver Options</b>	DALI
<b>Drive Current Range</b>	300mA 500mA
<b>Operating Voltage</b>	220-240V
<b>Electrical Class</b>	Class I Class II (on request)
<b>Operating Temperature Limit</b>	-25 °C to +40 °C

## Control

<b>Control Options</b>	Photocell Integral CMS Presence detector Integral 3-hour emergency
------------------------	---