

Kirium Wall product codes

	Codes	Example
Family		
Kirium	KIW	KIW
Light Engine		
8 LED	8	16
16 LED	16	
Drive Current		
300mA	300	300
500mA	500	
700mA	700	
Colour Temperature		
2700K	27	27
3000K	30	
4000K	40	
Distribution		
Narrow - Diamond+ A1 Optic	A1	A1
Medium - Diamond+ A5 Optic	A5	
Wide - Diamond+ C2 Optic	C2	
Glazing		
Clear	C	F
Frosted	F	
Product Colours		
RAL 7046 Mid grey	OF	DB
RAL 7035 Light grey	29	
RAL 9005 Black	10	
Other RAL colour [on request]	RAL [specify]	
Mounting		
Standard wall mounting (no BESA conduit)	NB	NB
For mounting over horizontal BESA conduit box	B	
Control		
No photocell	N	IUC
Photocell 35 lux (1:0.5)	U	
Part night switching Photocell 35 lux (1:0.5) (switch off midnight - 05:30) (Elexon regime 762)	A4	
Photocell 35 lux (1:0.5) + pre-programmed dimming (dimmed to 50% midnight - 05:30) (Elexon regime 531)	D8	
Integral CMS - Urban Control	IUC	
Integral CMS - Telensa	ITE	
Integral CMS - Mayflower	IMA	
Presence Detector (optional)		
Presence detector	PD	-
Emergency Version (optional)		
3-hour emergency	EM	-
Example code = KIW 16 300 27 A1 F DB NB IUC		

For further help with specifying a product, please [contact us](#)